








uPVC Drainage System

TECHNICAL MANUAL



BS EN 1329/1401



ISO 9001 FM 75767

Since it was established in 1976 Cosmoplast has become the market leading manufacturer of plastic piping systems in the Middle East. Through extensive product development, long term planning and substantial capital investment, Cosmoplast offers one of the most comprehensive and highest quality range of uPVC pipes and fittings for drainage applications.

Today the company has a turnover of more than \$ 100 million and supplies its products not only to the Gulf region but also throughout the Middle East, and specifically designed product ranges into Europe, Africa and the Far East.

Cosmoplast drainage systems include an extensive range of soil and waste pipes and fittings for commercial, industrial, housing and public sector developments.


Cosmoplast drainage systems include both solvent welded and push fit types applicable for wide and comprehensive range of

pipes and accessories. Having been pioneers in the development of drainage systems, Cosmoplast drainage systems represent the benchmark for quality product innovation and outstanding services.

Complete Solutions

With the wide range of pipes and fittings covering the size range from 20mm up to 1400mm, Cosmoplast now offers the most complete choice for its customers. The product range covers all the items required to complete any domestic and industrial drainage system.

Cosmoplast soil and drainage system is fully compatible with its above the ground and underground systems. This enables integrated above and below ground drainage systems to be designed, specified, and supplied from a single reliable source with confidence.



Advantages of Cosmoplast uPVC Drainage System

Advantages of Cosmoplast uPVC Drainage System:

All products supplied by Cosmoplast come with additional advantages like

- Proven research to suit customer's application needs.
- Precise manufacturing according to International Standards.
- ISO 9001 Quality System Accredited Manufacturing environment.
- Stringent testing to international standards.
- Technical service and consulting back up.
- Installation and jointing advice and services.
- Assured timely deliveries.
- Maintenance-free system and long-term reliability.



KITE MARKED PIPES AND FITTINGS QUALITY ASSURED PRODUCTS

Cosmoplast drainage systems are manufactured according to the latest European Standards, and are subject to very strict Quality Policy supervised by BSI which enabled Cosmoplast systems to be approved by the most prestigious International Institutes.

Cosmoplast Underground and Above Ground Drainage Pipes & Fittings are approved by the British BSI and are awarded the Kite Mark Quality Certificate where applicable.



ISO 9001 FM 75767



BSEN 1329



BSEN 1401-01



NEW EUROPEAN STANDARDS (EN STANDARDS)

COSMOPLAST uPVC drainage pipes and fittings are manufactured and tested in accordance with the new British - European Standards BS EN which have replaced the old British Standards for drainage applications. The new BS EN standards cover all the sizes and applications of the BS Standards.

BS EN 1329 : 2000

applies to uPVC piping systems for soil and waste discharge (low and high temperature) within the building structure. This standard replaces the British Standards BS5255 and BS4514. Products made to BS EN1329 are fully compatible with the products made to BS5255 and BS4514.

BS EN1401-1:1998

applies to uPVC piping systems for underground drainage and sewerage. This standard has replaced most of BS4660 and all of BS5481. Products made to BS EN1401-1 are fully compatible dimensionally with the products manufactured to BS 4660 and BS 5481.



BS EN 1329/1401




ISO 9001 FM 75767

Joining Techniques

SOLVENT CEMENT JOINTING

To achieve effective reliable joints:

1. Cut the pipe at right angle using appropriate cutter or saw.



2. Chamfer the pipe and remove the burrs and filings.



3. Clean the pipe and fitting with dry cloth and apply the cleaning fluid to the outside surface of the pipe and the inside surface of the fitting.



4. Apply thin layer of solvent cement to the mating surfaces using suitable brush.



5. While the solvent cement is still wet, insert the pipe inside the fitting until it reaches the socket end. It is recommended to twist the pipe a $\frac{1}{4}$ turn while inserting it inside the fitting for better distribution of the cement.



6. Wipe the excess cement and leave the joint to dry.



Note :

Applying excessive quantity of solvent cement should be avoided as it creates pool of cement on the internal surface of the pipe that will continue to corrode the surface and weaken the pipe and fitting and might cause the joint to fail at high pressure.

PUSH FIT JOINTING

1. Cut the pipe at right angle using appropriate cutter or saw.



2. Chamfer the pipe and remove the burrs and filings.

3. Clean the pipe and fitting with dry cloth



4. Apply thin layer of appropriate lubricant on the rubber ring using suitable brush.



5. Insert the pipe inside the fitting until it reaches the socket end, then withdraw the pipe 5 – 10mm (depending on the size) to allow for expansion / contraction.



6. Wipe the excess lubricant..



CUTTING THE PIPES

While cutting Cosmoplast uPVC pipes, the following instructions should be followed:

- Appropriate pipe cutter or saw should be used.
- Cut pipes square and perpendicular to its axis.
- After cutting pipes, remove all burrs from the cut end, and bevel the sharp cutting edge.



SOLVENT WELDING IN HOT WEATHER CONDITIONS :

During hot weather conditions of 35°C and above, special consideration should be given to the process of solvent Welding of UPVC pipes and fittings to ensure a leak proof joint.

Solvent cements contain high strength chemical solvent which evaporate faster at elevated temperatures and in windy conditions.

When PVC pipes are stored in open areas or under direct sunlight, the pipe surface temperature will be around 15°C higher than the ambient temperature. The solvent cement attacks the hot surface faster and deeper. Therefore, it is very important to avoid using excess cement during the jointing process to avoid creating pools of cement inside the fitting and pipe sockets. Excess solvent cement should be wiped off the joined surface quickly.

Recommendations for the solvent welding during hot weather confitions:

1. Solvent cement and cleaners should be stored in a cool or shady areas.
2. Pipes and Fittings should be stored in a shady area before solvent welding
3. The surfaces to be joined should be cooled by wiping with a wet cloth. The surfaces should be dry before applying the solvent cement.
4. Solvent welding is recommended to be done during the cooler morning hours.
5. The two surface should be joined quickly while they are still wet with cement.
6. Shake or stir the solvent cement well before use.
7. Allow at least 24 hours for the joints to cure before pressurizing the system. For sizes above 8" you should allow at least 48 hours.

SUPPORT AND EXPANSION

- All pipework must be adequately supported whether vertical or horizontal.
- Plastic pipework expands and contracts with changes in temperature - whether ambient temperature or from the nature of the discharge through the pipework. Expansion joints must therefore be provided to accommodate such thermal movement.
- Horizontal pipework requires more frequent support than vertical pipework (for example, soil stacks)
- Suitable sound absorbing brackets with rubber lining should be used to support pipes. Those brackets must be dimensionally compatible to the pipe diameter. The fixed bracket creates fixed point in the pipe system.
- With fixed brackets the pipe or fitting can not be moved through the bracket after screws are tightened. In order to prevent sliding down of vertical pipes, each individual pipe must be secured on one point by a fixed bracket.
- Every horizontally installed pipe should always be fixed with one fixed bracket. All remaining pipe brackets in horizontal as well as in vertical installation must be tightened in such a way to allow sliding.
- Fixed brackets must be installed directly above the fitting at the bottom of the pipe end. The sliding bracket must be installed at a distance of maximum of two meters above the fixed bracket.
- Pipe brackets should not be installed in areas of diameter reduction and change of directions in the system, this is required to allow for the thermal expansion.
- Pipe brackets should be fixed on building materials with high strength in order to assure strong and durable pipe fixing.
- It is recommended that only steel brackets (ie. not plastic brackets) be used on interior soil stacks which are subjects to fire regulations
- Any point where pipework passes through a floor or wall and is made as a fire stop, it must be treated as a fixed point for the purposes of determining positions of expansion joints.



SUPPORT DISTANCES

	Maximum Support Distance	
	Vertical	Horizontal
Pipe Size - Soil		
82 mm	2 m	1 m
110 mm	2 m	1 m
160 mm	2 m	1.2 m
Pipe Size - Waste		
32 mm	1.2 m	0.5 m
40 mm	1.2 m	0.5 m
50 mm	1.2 m	0.5 m

EXPANSION IN uPVC PIPES

The PVC piping systems expand and contract with changes in temperature, both from ambient temperature and from the temperature of the fluid passing through the pipework.

The following sections explain the techniques of estimating and treating the expansion in PVC pipes.

Calculation of Expansion

The co-efficient of linear expansion of PVC pipes is relatively small compared to other plastic materials. However, the effects of thermal expansion in the system should be compensated wherever necessary.

The thermal expansion in PVC straight sections can be calculated using the below formula:

$$\Delta L = \alpha \times L \times \Delta T$$

Where:

ΔL = expansion (mm)

α = co-efficient of linear expansion (mm/m/°C) = 0.08

L = length of the pipe (m)



ΔT = temperature difference (°C)

Support and Expansion Distances

In general, rubber ring pipework (Push Fit) do not require expansion joints, as the rubber sockets in the fittings and pipes are acting as expansion joints to absorb the expansion and contraction.

While in solvent welding pipework, the expansion should be calculated and compensated as described below.

After calculating the thermal expansion in the PVC pipes, expansion couplers (Rubber ring couplers) should be installed in proper locations to absorb the change in pipe length.




VERTICAL INSTALLATIONS

Vertical Installations can be done in two ways:


a) Fixed Installation

b) Free Installation



HORIZONTAL INSTALLATIONS

In horizontal Installations, pipe clamps should be placed at intervals which are approximately ten times bigger than the pipe diameter. This will ensure that the installation is fixed and will not bend.




FP= Fixed point

SP= Sliding point


\varnothing = Pipe Diameter

VENTILATION


Ventilation is essential in every drainage system. In order to prevent traps being emptied by suction or pressure, both overpressure and underpressure should not exceed 300 Pa (30 mm water column). Air should be able to escape from the system (venting) and to enter the system (admittance). A ventilated discharge pipe is used for this purpose.



Technique (1)




Technique (2)



Technique (3)

CROSS-FLOW PREVENTION

When connecting small waste pipes to vertical discharge stacks, attention should be given to avoid the cross-flow from one branch to the other. The restricted entry zone (L) for the opposite waste pipe varies depending on the stack diameter, within which no connections should be made. However, connections are allowed at right angles of the boundary center line or directly opposite.



Stack Dia.	L (mm)
82	90
110	110
160	250

In case of cross flow from a large diameter to a small waste pipe, the cross flow should be prevented by connecting the waste pipe at or above the center line of larger branch. Connections are not allowed at right angles of boundary center line or directly opposite. In this case the restricted entry zone is always 200mm regardless of stack diameter.

RAINWATER OUTLETS (ROOF DRAINS)

Cosmoplast product range includes different models and options of rainwater outlets like the dome type, corner type, flat type...etc. they are all suitable for roofs with and without waterproofing systems.

All Cosmoplast roof drains are connected to the rainwater pipes without traps.



The corner type rainwater outlet enables both side and bottom connections to the rainwater pipes.

The gratings of all Cosmoplast rainwater outlets are connected to the uPVC body by screws which allow easy access to the rainwater pipes in case of maintenance or cleaning.

ACCESS FITTINGS

Access fittings should be installed at proper accessible locations in the system to enable cleaning and discharging any blockage that may occur in the system due to solid deposits.

These access fittings enable the insertion of cleaning hoses and springs whenever blockage occurs.

Access pipes are recommended to be installed on stack pipes at every 3 to 4 stories to enable multiple access points to the stack and allow the whole stack to be cleaned if needed.



Access fittings are also recommended to be installed at the points of connection between underground and above ground pipework, after pipework sections that include multiple bends and long pipe runs and on pipeworks which are casted in concrete.

TESTING DRAINAGE SYSTEMS

Drainage installations should be tested for leaks and defects in new installations and whenever the existing installation is altered, extended or repaired.

All new installations or modified portions should be left uncovered until the testing is successfully completed and approved.

Drainage systems are commonly tested by water and in some cases air test is done.

The following are some guidelines for testing drainage systems, while the local codes of practice for each country should be also noted and applied.

WATER TEST

- All pipe ends and connections must be plugged using suitable testing plugs.
- Install vertical pipe length to the drain to provide the necessary testing water head.
- Fill the system with water to maximum height of 3m (30 kPa).
- The maximum head at the lower parts of the system should never exceed 4.0m, therefore in case of steep gradients the system should be tested in sections.
- The filled system should be left 2 hours under testing, during which the system should be inspected by measuring the drop in water height.
- The pipe work should be inspected for any leakage and all defected installations should be repaired and tested again.



- Provide side support with 75mm wide battens at 1m centers.
- Maximum stack (normal conditions): seven layers high.
- Ideally, stacks should contain one diameter pipe size only. Where this is not possible, stack largest diameter pipes at base of stack. Small pipes may be nested inside larger pipes.
- If stored in the open for long periods or exposed to strong sunlight, cover the stack with opaque sheeting.
- Store fittings under cover. Do not remove from cartons or packaging until required.
- Store solvent cement and cleaning fluid in a cool place out of direct sunlight and away from any heat source.


Storage in hot climates

- Ultra-violet light can affect pipes and fittings: pipe colour may change and rubber seals may be degraded
- Accordingly:
 - » store all materials in well-ventilated, shady conditions
 - » do not expose to direct sunlight
 - » keep fittings in original packaging until required for use
- Maximum stack (hot conditions) six layers high .

Transport

While transport, pipes should be arranged safely on trucks avoiding crossing, bending and over stacking.

The pipes should also be fully supported over their total length.



GOOD SITE PRACTICE

Handling


- Take all reasonable care when handling uPVC, particularly in very cold conditions when the impact strength of the material is reduced.
- Do not throw or drop pipes, or drag them along hard surfaces.
- In case of mechanical handling, use protective slings and padded supports. Metal chains and hooks should not make direct contact with the pipe.

On-site Storage



- Stack pipe lengths:
 - » either on a flat base
 - » or on a level ground
 - » or on 75mm x 75mm timber at 1m max. centers.

RECOMMENDATIONS


a) The pipe must be cut with a fine saw. Big saw teeth would damage the pipes. The cut has to be vertical.




b) The pipe ends should be smoothly chamfered to an angle of 15° to ensure better jointing and avoid damaging the rubber ring.





c) It is not recommended to shorten the fittings as it could result in defective joints.






d) Connected pipes and fittings need to be fitted straight. Otherwise it could result in leakage at sealing points.



e) Before covering the pipes with concrete, it is recommended to cover the joints so that cement d'nt enter the joint.



f) Pipes must be correctly connected considering the expansion. Too shallow connections into the cap do not guarantee a safe joint, while too deep connections do not allow expansion.



MATERIAL PROPERTIES

The following table shows the main physical and thermal properties of the uPVC material:

Property	Value	Conditions and Remarks
Physical properties		
Molecular weight (resin)	140,000	cf: K57 PVC 70,000
Relative density	1.42 - 1.48	cf: PE 0.92 - 0.96, GRP 1.4 - 2.1, CI 7.20, Clay 1.8 - 2.6
Water absorption	0.12%	23°C, 24 hours cf: AC 18 - 20% AS1711
Hardness	80	Shore D Durometer, Brinell 15, Rockwell R 114, cf: HDPE 60
Impact strength - 20°C	20 kJ/m ²	Charpy 250 µm notch tip radius
Impact strength - 0°C	8 kJ/m ²	Charpy 250 µm notch tip radius
Coefficient of friction	0.4	PVC to PVC cf: PE 0.25, PA 0.3
Mechanical properties		
Ultimate tensile strength	52 MPa	AS 1175 Tensometer at constant strain rate cf: PE 12-20
Elongation at break	50 - 80%	AS 1175 Tensometer at constant strain rate cf: PE 500-900
Short term creep rupture	44 MPa	Constant load 1 hour value cf: PE 10-16
Long term creep rupture	28 MPa	Constant load extrapolated 50 year value cf: PE 6-12
Elastic tensile modulus	3.0 - 3.3 GPa	1% strain at 100 seconds cf: PE 0.6-0.8
Elastic flexural modulus	2.7 - 3.0 GPa	1% strain at 100 seconds cf: PE 0.5-0.7
Long term creep modulus	0.9 - 1.2 GPa	Constant load extrapolated 50 year secant value cf: PE 0.1 - 0.3
Shear modulus	1.0 GPa	1% strain at 100 seconds
Bulk modulus	4.7 GPa	G=E/2/(1+µ) cf: PE 0.2
Poisson's ratio	0.4	1% strain at 100 seconds K=E/3/(1-2µ) cf: PE 2.0 Increases marginally with time under load. cf: PE 0.45
Electrical properties		
Dielectric strength (breakdown)	14 - 20 kV/mm	Short term, 3 mm specimen
Volume resistivity	2 x 10 ¹⁴ Ω.m	AS 1255.1
Surface resistivity	10 ¹⁴ - 10 ¹⁶ Ω	AS 1255.1
Dielectric constant (permittivity)	3.9 (3.3)	50 Hz (10 ⁶ Hz) AS 1255.4
Dissipation factor (power factor)	0.01 (0.02)	50 Hz (10 ⁶ Hz) AS 1255.4
Thermal properties		
Softening point	80 - 84°C	Vicat method AS 1462.5 (min. 75°C for pipes)
Max. continuous service temp.	60°C	cf: PE 80, PP 110
Coefficient of thermal expansion	0.08	mm/m°C cf: PE 18 - 20 x 10 ⁻⁵ , CI 1.2 x 10 ⁻⁵
Thermal conductivity	0.16 W/(m.K)	0 - 50°C
Specific heat	1,000 J/(kg.K)	0 - 50°C
Thermal diffusivity	1.1 x 10 ⁻⁷ m ² /s	0 - 50°C
Fire performance		
Flammability (oxygen index)	45%	ASTM D2683 Fennimore Martin test, cf: PE 17.5, PP 17.5
Ignitability index	10 - 12 (/20)	cf: 9 - 10 when tested as pipe AS 1530 Early Fire Hazard Test
Smoke produced index	6 - 8 (/10)	cf: 4 - 6 when tested as pipe AS 1530 Early Fire Hazard Test
Heat evolved index	0	
Spread of flame index	0	Will not support combustion. AS 1530 Early Fire Hazard Test

1 - Corrosion resistance:

uPVC being a non-conductor is totally resistant to all types of galvanic and electromechanical influences which might corrode it. Being non-metallic, uPVC is resistant to any type of corrosion caused by water as well as a large range of industrial liquids and chemicals. Seepage from high sulphate soils as well as low hardness waters also do not threaten it. This in turn translates into a longer installed life of the uPVC pipe systems.

2 - Resistance to Abrasion:

uPVC pipes are highly resistant to abrasion due to stress from abrasion fluids of excessive pressure. Tests have shown that uPVC pipes are up to 2.5 times more resistant to abrasions when compared to steel.

3 - Resistance to biological attack and growth:

uPVC is completely resistant to any microscopic life that it might be exposed to. It does not offer a nourishing source to any bacterial life form and is completely guaranteed to withstand any such growth.

4 - Reaction with Building Materials:

uPVC does not react with any of the normal building materials like cements and paints . However, information about the chemical resistance of uPVC to a wide range of chemicals can be found in the tables of Chemicals Resistance listed in this catalogue.

5 - Thermal Expansion

The coefficient of linear expansion for uPVC is 0.08 mm/m/°K which means less than 1mm per each 1m length in case of a temperature rise of 10°C.

The thermal expansion in drainage systems should be treated by using push fit (rubber rings) fittings and sockets which should be located in suitable locations (BSEN 12056 - Code of Practice for Sanitary Pipework).

6 - Effect of sunlight:

Long exposure to sunlight causes the colour of uPVC to fade, in addition to the reduction of impact strength. The effect of sunlight does not seriously affect the performance of the system, however it is always advisable to protect the system from the direct exposure to sunlight by painting the exposed parts with any exterior glass paint (paint specialists can recomend the suitable types).

7 - Effect of frost:

The uPVC is not affected by frost, however sub-zero temperatures reduce the impact strength of the uPVC system. Therefore, extra care is to be given while handling and installing uPVC during sub-zero temperatures.

8 - Fire Hazard of uPVC Material:

uPVC pipes and fittings as finished products are not classified as hazardous to health as they exhibit no chemical hazards when used under normal conditions and applications.

uPVC pipes and fittings should be stored in dry and covered places and protected from direct sources of heat and sunlight. It should be noted that the packing cartons and pallets can form a fire risk and may participate in fire spread.

9 - Flammability

uPVC is self-extinguishing material as per BS2782 and fire rated as Class 1 as per BS476 - Part 7 and Class 0 to Part 6.

Due to its flame retardant property, uPVC finished products do not participate in fire. uPVC products have a higher ignition temperature than most of the other thermoplastic and organic materials.

When burns, uPVC form a protective char layer, which in turn act as an insulation layer that stops oxygen.

10 - Fire Fighting

All common fire extinguishers can be used effectively for fighting fires involving PVC.

Chemical Resistance of uPVC

The uPVC material has a high resistance to a wide range of chemicals which makes the uPVC as an ideal option for many residential and industrial applications.

Detailed tables for the chemical resistance of uPVC material can be provided upon request.



uPVC Soil, Waste and Above Ground Discharge System

Cosmoplast soil, waste and above ground drainage pipes and fittings are manufactured according to the latest European Standard BS EN 1329-1 from grey unplasticised polyvinyl chloride uPVC in sizes 32 mm to 315 mm.

Size 32 mm to 56 mm according to BS 5255 are manufactured from mUPVC or ABS.

Cosmoplast soil, waste and above ground drainage systems are available in two options:

1. Solvent Welding Type: with sizes from 36 mm up to 200 mm.
2. Rubber Ring (Push Fit) Type: with sizes from 40 mm up to 315 mm.

Both options are suitable for domestic drainage and particular requirements of commercial, industrial and public installations.

BSEN 1329 - 1 uPVC Drainage Pipes for Above Ground Drainage

Normal Size (mm)	W.T. (mm)	O.D. (mm)		Wall Thickness (mm)	
		min	max	min	max
32	3.00	32.00	32.20	3.00	3.50
36	3.00	36.20	36.45	3.00	3.50
40	3.00	40.00	40.20	3.00	3.50
43	3.00	42.75	43.05	3.00	3.50
50	3.00	50.00	50.20	3.00	3.50
56	3.00	55.80	56.05	3.00	3.50
75	3.00	75.00	75.30	3.00	3.50
82	3.00	82.00	82.30	3.00	3.50
110	3.20	110.00	110.30	3.20	3.80
160	3.20	160.00	160.40	3.20	3.80
200	4.90	200.00	200.50	4.90	5.60
250	6.20	250.00	250.50	6.20	7.10
* 315	7.70	315.00	315.60	7.70	8.70

* Produced upon request only.

BS 5255 - mUPVC and ABS Waste Pipes

Normal Size (mm)	W.T. (mm)	O.D. (mm)		Wall Thickness (mm)	
		min	max	min	max
1¼" / 36mm	1.80	36.15	36.45	1.80	2.20
1½" / 43mm	1.90	42.75	43.05	1.90	2.30
2" / 56mm	2.00	55.75	56.05	2.00	2.40

DIN19531 - 10; uPVC Pipes for Drainage Systems Inside Buildings

Normal Size (mm)	W.T. (mm)	O.D. (mm)		Wall Thickness (mm)	
		min	max	min	max
50 mm	1.80	50.00	50.20	1.80	2.20
75 mm	1.80	75.00	75.30	1.80	2.20




BS EN 1329/1401



ISO 9001 FM 75767


Solvent Welding Joints

uPVC Drainage Pipe




Nominal O.D. (mm)	Length (m)
* 36	4
40	4
* 43	4
50	4
* 56	4
75	5.8 / 6
82	5.8 / 6
110	5.8 / 6
160	5.8 / 6
200	5.8 / 6

Straight Coupler




D (mm)	L (mm)
* 36	45
* 43	45
50	52
* 56	56
75	83
82	96
110	112
160	161
200	140

87.5° Elbow




D (mm)	L (mm)
* 36	77
* 43	90
50	101
* 56	100
75	137
82	170
110	190
160	329
200	305

45° Elbow




D (mm)	L (mm)
* 36	67
* 43	83
50	86
* 56	94
75	128
82	139
110	170
160	269
200	290

45° Y Branch




D (mm)	L (mm)
* 36	102
* 43	115
50	125
* 56	144
75	192
82	205
110	268
160	337
200	400

45° Reducer Y Branch




D (mm)	d (mm)	L (mm)
75	50	156
82	56	178
110	50	175
110	56	186
110	75	209
110	82	223
160	110	380
200	160	400

87.5° Tee Branch



D (mm)	L (mm)
* 36	90
* 43	109
50	106
* 56	132
75	167
82	176
110	250
160	358
200	365


87.5° Reduced Tee



D (mm)	d (mm)	L (mm)
75	50	143
82	56	165
110	50	156
110	56	168
110	75	187
110	82	199
160	110	251
200	160	360


* Available in UPVC and ABS

Reducer Bush




D (mm)	d (mm)	L (mm)
* 43	36	27
56	36	27
* 56	43	27
75	50	43
82	43	37
82	56	37
110	50	52
110	56	50
110	75	52
110	82	50
160	75	62
160	110	62
200	160	60

45° Access Elbow




D (mm)	L (mm)
43	83
56	94
82	139
110	170
160	269

87.5° Access Elbow




D (mm)	L (mm)
43	93
50	94
56	100
75	133
82	170
110	190
160	329

87.5° Access Tee




D (mm)	L (mm)
43	109
56	132
82	205
110	250
160	358

Access Pipe




D (mm)	L (mm)
50	102
75	160
82	212
110	219
160	256

Access Plug



D (mm)	L (mm)
40	75
* 43	50
50	75
* 56	50
75	89
82	77
110	88
160	95
200	100

Pipe Access Plug & Cap




D (mm)	L (mm)
36	47
43	52
50	51
56	55
75	69
82	75
110	80
160	95

Double Tee with Access




D (mm)	d (mm)	L (mm)
110	110	219



Floor Trap with Removable Separator



D (mm)	d (mm)	d1 (mm)	H (mm)
110	82	43	140




Body Material can be:
- UPVC
- ABS

50 mm seal depth

Floor Trap with Removable Separator



D (mm)	d (mm)	d1 (mm)	H (mm)
110	82	43	170




Body Material can be:
- UPVC
- ABS

70mm Seal depth

Deep Seal Floor Trap



D (mm)	d (mm)	d1 (mm)	H (mm)
110	82	56	175




Body Material can be:
- UPVC
- ABS

75mm Seal Depth

Metric Floor Trap



D (mm)	d1 (mm)	d2 (mm)	H (mm)	H1 (mm)
110	75	50	162	56.5




Body Material can be:
- UPVC
- ABS

70mm Seal dept

Short Floor Trap



D1 (mm)	d2 (mm)	d3 (mm)	H (mm)
110	82	43	108
110	82	56	108




40mm Seal Depth

160 mm Floor Trap



D1 (mm)	d2 (mm)	d3 (mm)	H (mm)
160	110	50	160
160	110	56	160




70mm Seal Depth

Boss Pipe MXF




D (mm)	d1 (mm)	d2 (mm)	L (mm)
110	56	43	209




Boss Pipe FXF



D (mm)	d1 (mm)	d2 (mm)	L (mm)
110	56	43	209



Boss Connector




Ø	D (mm)	L (mm)
160	56	43
160	43	36
110	56	50
110	43	0

AC to Drainage Boss




D (mm)	d	L (mm)	F (mm)
43	1"	41	52



AC to Drainage Boss




D (mm)	d1	d2	L (mm)
56	1"	3/4"	34



45° Double Y Branch




D (mm)	d (mm)	L (mm)
50	50	128
75	75	193
110	110	260
160	160	260



87.5° Double Tee Branch





D (mm)	d (mm)	L (mm)
50	50	106
75	75	166
110	110	219
160	160	219




Flat Roof Drain



d (mm)	D (mm)	L (mm)
82	178	40



Vent Cowl





D (mm)	L (mm)
50	63
56	70
75	84
82	85
110	105
160	138

Rainwater Outlet





d (mm)	D (mm)	L (mm)
82	180	115
110	343	117



Dome Type Rainwater Outlet (HD)




d (mm)	D (mm)	L (mm)
82	405	168
110	405	168



Rain Water Outlet With Extension





D (mm)	d (mm)	H (mm)
110	270	146



Corner Roof Outlet



D (mm)	H (mm)	W (mm)
82	154	194
110	154	194




Balcony Drain With Side Outlet



Z (mm)	D (mm)	d (mm)	L (mm)
100	56	50	68
150	56	50	70


Material : ABS



Female Adapter




D (mm)	L (mm)	T
36	47	1¼"
43	52	1½"
43	57	2"



Male Adapter




D (mm)	L (mm)	T
36	47	1¼"
43	52	1½"
43	57	2"



Shower Elbow




D (mm)	d	L (mm)
43	1½"	56



Reducer For Shower Elbow




D (mm)	d (mm)	L (mm)	L1 (mm)	L2 (mm)
56	43	52.5	25	25



Pipe Plug



D (mm)	H (mm)
43	20
56	25
82	35
110	40
160	50



Non-Pressure End Cap




D (mm)	H (mm)
56	23
82	28
110	30
160	32
200	40



uPVC Floor Trap Cover Model(1)




D (mm)	Z (mm)	L1 (mm)
110	150	27.5




uPVC Floor Trape Cover - Model (2)




L (mm)	Z (mm)	D (mm)
148	22	110



Floor Trap Mesh




L (mm)	Z (mm)	D (mm)
150	16	102



uPVC Floor Clean Out




D (mm)	Z (mm)	L (mm)
110	150	27.5



Rodding Eye Cover




D (mm)	W (mm)
82	146
110	146



Stainless Steel Floor Clean Out



D (mm)	Z (mm)	L (mm)	t (mm)
110	150	27,5	2m
110	150	27,5	3m




available in SS 304 & 316

Stainless Steel Drain Cover



D (mm)	Z (mm)	L (mm)	t (mm)
110	150	27,5	2m
110	150	27,5	3m




available in SS 304 & 316

SS Balcony Drain Cover



Z (mm)	D (mm)	L (mm)	t (mm)
79	50	16	2



Rubber Ring (Push-Fit) Joints

Cosmoplast pipes and fittings with rubber ring (push-fit) joints present many advantages, like the ease of installation especially in tight places. It also gives the connections the freedom to expand and contract without affecting the joint quality.

The sealing rings used in producing Cosmoplast push fit joints are made of natural / synthetic rubber, offering chemical resistance to wide range of chemicals. The rings also provide an effective seal against internal and external water pressure and against penetration by tree roots.

uPVC Drainage Pipe




D (mm)	L (mm)
40	5,8 / 6m
50	5,8 / 6m
56	5,8 / 6m
75	5,8 / 6m
82	5,8 / 6m
110	5,8 / 6m
160	5,8 / 6m
200	5,8 / 6m
250	5,8 / 6m
315	5,8 / 6m



87.5° Elbow "Push Fit"




D (mm)	d (mm)	L (mm)
40	40	113
50	50	125
56	56	133
75	75	170
82	82	168
110	110	225
160	160	308
200	200	373
* 250	* 250	430



87.5° Long Elbow "Push Fit"




D (mm)	d (mm)	L (mm)
82	82	168
110	110	225



45° Elbow "Push Fit"




D (mm)	d (mm)	L (mm)
40	40	130
50	50	137
56	56	174
75	75	146
82	82	168
110	110	220
160	160	287
200	200	325
* 250	* 250	440



45° Y Branch "Push Fit"




D (mm)	d (mm)	L (mm)
40	40	164
50	50	183
56	56	203
75	75	238
82	82	235
110	110	290
160	160	421
200	200	490
* 250	* 250	660



45° Reduced Y Branch "Push Fit"




D (mm)	d (mm)	L (mm)
75	50	212
110	75	276
110	82	256
160	110	325
200	110	360
200	160	490
* 250	160	490
* 250	200	540



87.5° Tee "Push Fit"



D (mm)	d (mm)	L (mm)
40	40	164
50	50	174
56	56	169
75	75	215
82	82	168
110	110	280
160	160	407
200	200	410
* 250	* 250	560





* Not Manufactured by Cosmoplast




ISO 9001 FM 75767

87.5° Reduced Tee "Push Fit"




D (mm)	d (mm)	L (mm)
75	50	191
110	50	188
110	75	236
110	82	224
160	110	325
200	160	370

Coupler "Push Fit"




D (mm)	L (mm)
40	110
50	110
56	108
75	131
82	113
110	159
160	168
200	230
250	270

Repair Coupler "Push Fit"




D (mm)	L (mm)
50	110
56	108
75	131
82	115
110	159
160	168
200	230
250	270

Single Socket "Push Fit"




D (mm)	d (mm)	L (mm)
82	82	110
110	110	129
160	160	151

Reducer "Push Fit"




D (mm)	d (mm)	L (mm)
50	40	124
75	50	143
82	56	110
110	50	143
110	56	133
110	75	175
110	82	133
160	110	173
200	160	275
* 250	200	260
* 250	160	370

87.5° Double Tee "Push Fit"




D (mm)	d (mm)	L (mm)
82	82	206
110	110	280
160	160	360

45° Double Y Branch "Push Fit"



D (mm)	d (mm)	L (mm)
56	56	195
82	82	235
110	110	287
160	160	401

Floor Trap "Push Fit"



D (mm)	D1 (mm)	d (mm)	L (mm)
110	82	56	175
110	75	50	171
110	75	40	171

75mm Seal Depth

* Not Manufactured by Cosmoplast




BS EN 1329/1401




ISO 9001 FM 75767

Access Pipe "Push Fit"




D (mm)	d (mm)	L (mm)
82	82	214
110	110	320
160	160	350

87.5° Access Elbow "Push Fit"




D (mm)	d (mm)	L (mm)
82	82	168
110	110	225

87.5° Access Tee "Push Fit"




D (mm)	d (mm)	L (mm)
82	82	168
110	110	280

Access Plug "Push Fit"




D (mm)	L (mm)
40	75
43	50
50	75
56	50
75	89
82	77
110	88
160	95
200	100

Pipe Access Plug & Cap



D (mm)	L (mm)
36	47
43	52
50	50
56	55
75	72
82	75
110	80
160	95

Pipe Plug




D (mm)	L (mm)
40	48
50	50
56	
75	60
43	20
56	25
75	
82	35
110	40
160	50

End Cap



D (mm)	H (mm)
56	23
82	28
110	30
160	32
200	40
250	50
315	60

HDPE Aerator (Speed Breaker) with Rubber Ring Socket



D	H (mm)	L (mm)
110	270	850
160	280	900

Underground Drainage And Sewerage System

Cosmoplast underground drainage and sewerage system is manufactured from Golden Brown unplasticised polyvinyl chloride uPVC Material.

Cosmoplast underground drainage system is available in two options:

1. Solvent Welding Type: with sizes from 75 mm up to 200 mm.
2. Rubber Ring (Push Fit) Type: with sizes from 40 mm up to 1000 mm.

Cosmoplast underground uPVC pipes and fittings are manufactured according to the latest European Standard BS EN 1401 BSEN 1401 - 1 uPVC Pipes for Underground Drainages :


Mean Outside Diameter		SN 2 SDR 52		SN 4 SDR 41		SN 8 SDR 34	
min	max	e _{min}	e _{m, max}	e _{min}	e _{m, max}	e _{min}	e _{m, max}
110	110.3	-	-	3.2	3.8	3.2	3.8
125.0	125.3	-	-	3.2	3.8	3.7	4.3
160.0	160.4	3.2	3.8	4.0	4.6	4.7	5.4
200.0	200.5	3.9	4.5	4.9	5.6	5.9	6.7
250.0	250.5	4.9	5.6	6.2	7.1	7.3	8.3
315.0	315.6	6.2	7.1	7.7	8.7	9.2	10.4
*355.0	355.7	7.0	7.9	8.7	9.8	10.4	11.7
400.0	400.7	7.0	8.9	9.8	11.0	11.7	13.1
*450.0	450.8	8.8	9.9	11.0	12.3	13.2	14.8
500.0	500.9	9.8	11.0	12.3	13.8	14.6	16.3
630.0	631.1	12.3	13.8	15.4	17.2	18.4	20.5
*710.0	711.2	13.9	15.5	17.4	19.4	-	-
800.0	801.3	15.7	17.5	19.6	21.8	-	-
*900.0	901.5	17.6	19.6	22.0	24.4	-	-
1000.0	1001.6	19.6	21.8	24.5	27.2	-	-

Note : 40mm, 50mm, 75mm & 82mm sizes according to BSEN1329 can be produced in orange colour.

* Pipes to these nominal sizes are not normally available in stock.


Push Fit Fittings

uPVC "Push Fit"




D (mm)	L (m)
40	5.8/6
50	5.8/6
56	5.8/6
75	5.8/6
82	5.8/6
110	5.8/6
160	5.8/6
200	5.8/6
250	5.8/6
315	5.8/6
400	5.8/6
500	5.8/6

87.5° Elbow "Push Fit"




D (mm)	d (mm)	L (mm)
40	40	113
50	50	125
56	56	133
75	75	140
82	82	168
110	110	225
160	160	308
200	200	373
* 250	250	430
* 315	315	510
* 400	400	640
500	500	Fabricated

87.5° Long Elbow "Push Fit"



D (mm)	d (mm)	L (mm)
82	82	168
110	110	225

45° Elbow "Push Fit"



D (mm)	d (mm)	L (mm)
40	40	130
50	50	137
56	56	174
75	75	146
82	82	168
110	110	220
160	160	287
200	200	325
* 250	250	440
* 315	315	520
* 400	400	650
500	500	Fabricated




* Not Manufactured by Cosmoplast




ISO 9001 FM 75767

45° Y Branch "Push Fit"




D (mm)	d (mm)	L (mm)
40	40	164
50	50	183
56	56	203
75	75	238
82	82	235
110	110	290
160	160	421
200	200	490
* 250	250	660
* 315	315	820
* 400	400	1030
500	500	Fabricated

45° Reduced Y Branch "Push Fit"




D (mm)	d (mm)	L (mm)
75	50	212
110	75	276
110	82	256
160	110	325
200	160	490
200	110	360
* 250	200	520
* 250	160	470

87.5° Tee "Push Fit"




D (mm)	d (mm)	L (mm)
50	50	174
56	56	169
75	75	215
82	82	168
110	110	280
160	160	407
200	200	410
* 250	250	560
* 315	315	680
* 400	400	880
500	500	Fabricated

87.5° Reduced Tee "Push Fit"




D (mm)	d (mm)	L (mm)
75	50	191
110	50	188
110	75	236
110	82	224
160	110	325
200	160	370

Coupler "Push Fit"




D (mm)	L (mm)
40	110
50	110
56	108
75	131
82	113
110	159
160	168
200	230
250	270

Repair Coupler Push Fit"




D (mm)	L (mm)
50	110
75	131
82	115
110	159
160	168
200	230
250	270
* 315	310
* 400	440
500	Fabricated

Single Socket "Push Fit"



D (mm)	d (mm)	L (mm)
82	82	110
110	110	129
160	160	151

Reducer "Push Fit"



D (mm)	d (mm)	L (mm)
50	40	124
75	50	143
82	56	110
110	75	175
110	82	133
160	110	173
200	160	275
* 250	160	370
* 250	200	260
* 315	250	300



BS EN 1329/1401

* Not Manufactured by Cosmoplast




ISO 9001 FM 75767

45° Double Y Branch "Push Fit"




D (mm)	d (mm)	L (mm)
82	82	235
110	110	287
160	160	401



87.5° Double Tee "Push Fit"




D (mm)	d (mm)	L (mm)
82	82	206
110	110	280



87.5° Access Tee "Push Fit"




D (mm)	d (mm)	L (mm)
82	82	168
110	110	280



Access Pipe "Push Fit"




D (mm)	d (mm)	L (mm)
82	82	214
110	110	320
160	160	350



87.5° Access Elbow "Push Fit"




D (mm)	d (mm)	L (mm)
82	82	168
110	110	225



Access Plug "Push Fit"




D (mm)	L (mm)
40	75
50	75
56	50
75	89
82	77
110	88
160	95
200	100



End Cap



D (mm)	H (mm)
82	28
110	30
160	32
200	40
250	50
315	60



Pipe Plug




D (mm)	L (mm)
40	48
50	50
56	
75	
82	35
110	40
160	50




Solvent Welding Joints

uPVC Drainage Pipe (ss)




D (mm)	L (m)
75	5.8/6
82	5.8/6
110	5.8/6
160	5.8/6
200	5.8/6

87.5° Elbow




D (mm)	L (mm)
50	101
75	137
82	170
110	190
160	329
200	305

45° Elbow




D (mm)	L (mm)
50	86
75	128
82	139
110	170
160	269
200	290

Coupler




D (mm)	L (mm)
50	52
75	83
82	96
110	112
160	161
200	140

87.5° Tee Branch




D (mm)	L (mm)
50	106
75	167
82	205
110	250
160	358
200	365

87.5° Reduced Tee




D (mm)	d (mm)	L (mm)
100	75	187
110	82	199
160	110	251
200	160	360

45° Y Branch



D (mm)	L (mm)
50	125
75	192
82	205
110	268
160	337
200	400

45° Reduced Y Branch




D (mm)	d (mm)	L (mm)
110	75	209
110	82	223
160	110	380
200	160	400

Double Y Branch




D (mm)	d (mm)	L (mm)
110	110	260
160	160	260
160	110	280



Double Tee Branch




D (mm)	d(mm)	L(mm)
110	110	219
160	160	217



Reducer Bush




D (mm)	d (mm)	L (mm)
75	50	
110	75	52
110	82	223
160	110	380
200	160	600



Access Plug & Cap




D (mm)	L (mm)
50	75
75	86
82	77
110	88
160	95
200	100



Pipe Access Plug & Cap




D (mm)	L (mm)
75	69
82	75
110	80
160	95



Access Pipe (Socket)




D (mm)	L (mm)
110	219
160	259



87.5° Access Elbow




D (mm)	L(mm)
75	133
82	170
110	190
160	329




45° Access Elbow



D (mm)	L(mm)
82	139
110	170
160	269




87.5° Access Tee




D (mm)	L(mm)
82	205
110	250
160	358

Bottle Trap




D (mm)	d (mm)	L (mm)
160	110	290

Gully Trap




D (mm)	d (mm)	L (mm)	H (mm)
160	110	290	150

Bottle Gully Trap




D (mm)	D1(mm)	d (mm)	d1(mm)	L (mm)
160	110	110	50	270

P Trap




D (mm)	d (mm)	L (mm)
110	110	290

Long P Trap Solvent




D1 (mm)	D2 (mm)	L (mm)	H (mm)	H1 (mm)
110	110	240	276	466

V-Type P Trap Rubber




D1 (mm)	D2 (mm)	L (mm)	H (mm)	H1 (mm)
110	110	303	216	245

V-Type P Trap Solvent




D1 (mm)	D2 (mm)	L (mm)	H (mm)	H1 (mm)
110	110	303	216	245

Square Hopper Grating



D (mm)	L(mm)	H (mm)	H1(mm)
110	164	98	25

Square Hoper With Extension



L(mm)	H(mm)	H1(mm)	D(mm)
170	198	100	110

Pipe Cleaner



Size (L)
½ L
1 L

Solvent Cement



Size (L)
¼ L
½ L
1 L

Rubber Joint Lubricant



Size (L)
1 L

Rubber Lined Pipe Clamp



Size (mm)
36
43
56
82
110
160
200

Unlined Pipe Clamp



Size (mm)
36
43
56
82
110
160

Testing Plug



Size (mm)
43 (38-48)
56 (49-60)
82 (73-85)
110 (94-110)
160 (146-163)
200 (191-211)

Straight W-Connector



D (mm)	D1(mm)	H(mm)
110	110	128

Offset WC Connector



D (mm)	D1(mm)	H(mm)	F(mm)
110	110	128	20
110	110	128	40

Heavy Duty Cover For Gully Trap



Z (mm)	d (mm)	d (mm)	H (mm)
173	110	160	50

COSMOPLAST UPVC INSPECTION CHAMBERS

Inspection chambers are necessary in every drainage installation for inspection, testing and removal of solids from the drainage system. Cosmoplast Inspection Chamber provides access to the drainage system allowing rodding in both directions.



DEPTH ADJUSTMENT:

The chamber depth can easily be accommodated by installing the chamber risers one over the other to achieve the desired height. The last chamber riser can be trimmed to suit the finished ground level.



COMPONENTS :

Inspection Chamber Base




DIMENSIONS (mm)						
D	C	L	L1	H	H1	H2
110	330	450	440	80	130	237

Inspection Chamber Riser




DIMENSIONS (mm)			
D	D1	D2	H
328	335	320	156




Inspection Chamber Cover




DIMENSIONS (mm)			
L	L1	L3	H
312	312	338	130



Inspection Chamber Blanking Plug



DIMENSIONS (mm)				
D	D1	D2	L	T
116	110	102	66	2



Inspection Chamber Rubber Seal




Perforated & Slotted Pipes

a) Perforated Pipes


Cosmoplast produces wide range of perforated uPVC pipes for Sub-soil drainage applications. The below sketches show the general configurations which may vary depending on size and class of pipe to be perforated.

Parameters	Limits of Variation	
Outside diameter	D	32mm to 630mm in standard sizes
Wall thickness	t	In accordance with the class of pipes selected
Longitudinal pitch of holes	p	30mm to 200mm depending on size and class of pipe
Hole Diameter	d	3mm to 10mm depending on size and class of pipe
Number of rows	n	1 to 4
Angular pitch of holes	a	40 degrees for 3 or 4 rows 40, 80 or 120 degrees for 2 rows

Straight rows



Staggered rows





WARRANTY

Cosmoplast uPVC pipes and fittings are subjected to continuous tests during production in order to guarantee high quality and reliability.

Cosmoplast Industrial Co. LLC guarantees that its uPVC Pipes & Fittings are free from manufacturing and material defects.

In witness hereof, Cosmoplast issues this warranty for its system of uPVC Pipes and Fittings which shall be valid for a period of ten years starting from the date of installation.

However, Cosmoplast will not accept, and will not be held liable or responsible for damage to these products, or any consequential losses under the following conditions:


1. If working conditions are different than those prescribed in this catalogues.
2. If the components are used in installations where the fluid is not compatible with the material as per the related international standards.
3. If the components present defects when installed, due to incidental factors easily recognizable at the time of installation or when the system is submitted to pressure test.
4. If Cosmoplast components are installed with other items not manufactured by Cosmoplast.
5. In case of poor or inappropriate storage.
6. In case of poor or inappropriate installation, use or operation.



b) Slotted pipes

Cosmoplast produces wide range of SLOTTED uPVC pipes for Sub-soil and Land drain

Cosmoplast uPVC slotted pipes have two rows of circumferential slots which are machine cut and staggered, the slots are cut at an angle of 45° to give a large open area free to carry water. Pipes are slotted to give maximum infiltration as detailed below.



SIZES	SLOT LENGTH		SLOT WIDTH		Min.No.of slot per	Min.slot Area	PITCH
	Min. mm	Max. mm	Min. mm	Max. mm	MTR/ROW		
110	63	65	2	4	13	4914	75
160	63	65	2	4	13	4914	75
200	76	78	2	4	13	5928	75
225	86	88	2	4	13	6864	75
250	98	100	2	4	13	7644	75
315	120	125	2	4	13	9360	75

Note:

The number of slot, slot width, length, pitch and pattern can be altered to suit specific requirements

Pipeline Systems



www.cosmoplast.com

Cosmoplast Industrial Co., A Subsidiary of Interplast Co. Ltd.

Sharjah

Sales Off. Tel: +971 6 5331212
 Fax: +971 6 5331917 / 5332901
 P.O. Box: 6032

Dubai

Tel: +971 4 8850500
 Fax: +971 4 8850700
 P.O. Box: 50488

Abu Dhabi

Sales off. Tel: +971 2 5515364
 Fax: +971 2 5515365
 P.O. Box: 8593

Saudi Arabia-Riyadh

Sales off. Tel: +966 1 4483344
 Fax: +966 1 4480246
 Email: info@cosmoplast-KSA.com

Qatar-Doha

Sales off. Tel: +974 4 4582290 / 1
 Fax: +974 4 4687886
 Email: infoq@cosmoplastq.com

Email: pipeline@cosmoplast.com, plumbing@cosmoplast.com

Version 1 / Issue 10 / November 2015